SONY

Professional Photo Printers and Photofinishing Solutions

Screen image simulated.

Print by Sony™

Our solutions come in different shapes and different sizes – ranging from those aimed at professional photographers looking to print beautiful, high-quality digital photos on-demand, a range of digital photofinishing systems ideally suited to retail outlets, business and commerce, walk-in ID photography and dozens of other business opportunities.

At Sony, we're making it easier and more affordable than ever before to provide digital photo services. The affordable prices of our professional photo printers and digital photofinishing systems mean that there is no longer a prohibitively high investment required to equip yourself with simple to use, top-quality professional equipment, making mini-labs, couriers and unsold prints a thing of the past. There really is no easier or better way to get into the professional digital photofinishing market than with Sony.

Prints anywhere, anytime for anyone. The digital revolution is here, and it's here for good. The market for digital cameras and camera phones has exploded, and with it, the number of digital photos taken. Millions of potential customers are looking for quick and easy ways to have their digital photographs printed. By offering your customers a professional photofinishing system that's quick, affordable and offers additional value-added services, you too could take a slice of this growing, profitable market.

Superior printing technology

We believe that when printing color photographs, there is nothing like dye sublimation. That's why all of our photofinishing systems are built upon this superior printing technology. It quite simply produces photo-realistic, continuous-tone images that look like they came from a photo lab, yet use no chemical processing like traditional photographs.

A thermal print head, consisting of thousands of heating elements, contacts the media being printed on and vaporizes the solid dyes. The resulting gas diffuses into the surface of the paper. What makes these printers unique is that the heating elements on the print head can be set to any one of 256 temperatures. This precise control of the amount of dye that's vaporized controls the intensity of the resulting dot on the paper and produces continuous-tone images. Other printing methods, such as ink jet, cannot gradate each dot and simply can't achieve the same results.

Sony Digital Photo Printer

Ink Jet Printer

Full-color prints

Only 6 colors

Table of contents

Retail Shop

UP-CR10L Page 5
SnapLab® Digital Photo Printer

Standalone printer for on-location applications

UP-CX1 Page 5
Digital Photo Printer

Affordable, high-volume greeting card printer

UPA-PC500 Page 6
Digital Photofinishing System

All-in-one system controller for countertop and kiosk systems

UP-DR200 Page 5
Digital Photo Printer

High-speed, high-volume printer with ProMatte™ finish

Compact PictureStation™ Page 6
Digital Photofinishing System

Fast prints in all sizes from all digital media; plus a photo scanner for print-to-print

UP-D75 Page 7
Digital Photo Printer

High-quality ProMatte 8 x 10″ sheet printer

Deluxe PictureStation Page 6
Digital Photofinishing System

Fast prints in all sizes from all digital media; plus a photo scanner for print-to-print

UP-GR700 Page 7
Digital Photo Printer

High-quality, high-speed ProMatte package printer

Event Photo

UP-DR200 Page 5
Digital Photo Printer

High-speed, high-volume printer with ProMatte finish

UP-D75 Page 7
Digital Photo Printer

High-quality ProMatte 8 x 10″ sheet printer

UP-CX1 Page 5
Digital Photo Printer

Affordable high-volume greeting card printer

UP-GR700 Page 7
Digital Photo Printer

High-quality, high-speed ProMatte package printer

UP-CR10L Page 5
SnapLab Digital Photo Printer

Standalone printer for on-location applications

Portrait Photo

UP-D75 Page 5
Digital Photo Printer

High-quality ProMatte 8 x 10″ sheet printer

UP-GR700 Page 5
Digital Photo Printer

High-quality, high-speed ProMatte package printer

Photo Kiosk

UP-CX1 Page 5
Digital Photo Printer

Affordable, high-volume greeting card printer

UP-DR200 Page 5
Digital Photo Printer

High-speed, high-volume printer with ProMatte finish

UP-D75 Page 5
Digital Photo Printer

High-quality ProMatte 8 x 10″ sheet printer

UP-GR700 Page 5
Digital Photo Printer

High-quality, high-speed ProMatte package printer

Passport/ID Photo

UPX-C200 Page 8
Digital Printing System

Flexible and efficient wireless passport ID photo printing system

UPX-C100 Page 8
Digital Printing System

Affordable passport ID photo printing system

Digital photofinishing

Sony digital photofinishing systems: scalable, flexible solutions for every retail environment.

UP-CX1
Digital Photo Printer

The UP-CX1 is a low-investment digital photo printer which makes no compromises in print quality. It can print in four different sizes at a superb 300 dpi, and fast – a 4 x 8 inch greeting card prints in just about 20* seconds. This, combined with its small size and portability, makes it ideal for event photography.

- Print 4 x 8" photo greeting cards with downloadable application
- Easy print media replacement
- Four print sizes (3.5 x 5", 4 x 6", 5 x 7", 4 x 8")
- Hi-Speed USB 2.0 interface for fast image transfer
- Low hardware investment

UP-DR200
Digital Photo Printer

Boost your business with high productivity and superb quality with the UP-DR200 professional photo printer. It delivers quality prints and rapid turnaround in event photography, producing 4 x 6 inch prints in under 8* seconds. Three print sizes are available in three different print finishes from the same print pack: Glossy, Texture, and ProMatte.

- High speed, high capacity, high volume
- Three print sizes available:
  - 4 x 6" prints in about 8* seconds, holds 700 prints
  - 5 x 7" prints in about 12.5* seconds, holds 400 prints
  - 6 x 8" prints in about 14.5* seconds, holds 350 prints
- Front operation
- Low-cost consumables

UP-CR10L SnapLab
Digital Photo Printer

The SnapLab Digital Photo Printer is a stylish, travel-sized standalone professional photofinishing solution. Packed with a host of robust features in a highly compact body, this digital photo printer produces photo-quality prints in just a few seconds. The 8 inch color LCD (viewable area measured diagonally) and intuitive touch-screen interface help you create memorable photos quickly and easily. The ability to edit photos on the spot with no need for a computer, makes the SnapLab printer the ideal choice for countless on-location applications.

- High speed printing in three print sizes:
  - 3.5 x 5" prints in about 13* seconds
  - 4 x 6" prints in about 16* seconds
  - 5 x 7" prints in about 17* seconds
- PC FREE editing tools included:
  - Add text and borders
  - Zoom, crop and rotate photos
  - Remove red eye in seconds
  - Create wallet-sized prints and collages
  - Transform color images into black and white or sepia-toned

**Does not include processing time.*

UPA-PC500
Digital Photofinishing Terminal

The UPA-PC500 is designed to form the core of your scalable, flexible digital photofinishing kiosk and countertop systems. Consisting of an intuitive touch-screen interface and inputs for today's most widely-used media, it can be set up for either customer self-service or for operation by staff. Start small and simple with just one printer connected or connect up to four Sony printers and a scanner to provide a full range of revenue-generating photofinishing services.

- Flexible customization of settings, prices, graphics
- Built-in receipt printer, memory card reader & DVD combo
- Easy-to-use photo editing tools
- Variety of outputs: borders, collage, scrapbook, portrait, index prints, CDs…

Compact PictureStation™
Digital Photofinishing System

Sony's Compact PictureStation System is designed as a full featured digital photo imaging kiosk, with a small footprint to fit anywhere! All standard photo sizes can be printed: Wallets, 3½ x 5, 4 x 6 , 5 x 7 and 8 x 10 inch photos, and 4 x 8 inch holiday cards. The Compact PictureStation System can create a single 4 x 6 print in under eight seconds* and can be expanded with the addition of two more high-speed printers. All Sony PictureStation Systems feature Sony's easy-to-use software designed for increased revenue opportunities, such as custom value packages, creative print options, and CD burning.

- Prints all standard photo sizes: Wallets, 3.5 x 5", 4 x 6", 5 x 7", 8 x 10" photos, and 4 x 8" holiday cards
- Integrated photo scanner for print-to-print pictures
- Small footprint for optimized retail spaces
- Connectivity options for remote monitoring, remote management, and credit card payment

Deluxe PictureStation
Digital Photofinishing System

Sony's Deluxe PictureStation System is our highest performance imaging kiosk, optimized for profitability! All standard photo sizes can be printed: Wallets, 3½ x 5, 4 x 6 , 5 x 7 and 8 x 10 inch photos, and 4 x 8 inch holiday cards. The Deluxe PictureStation System can be configured with up to four printers, creating over 1500 prints in an hour. All Sony PictureStation Systems feature Sony's easy-to-use software designed for increased revenue opportunities, such as custom value packages, creative print options, and CD burning.

- Prints all standard photo sizes: Wallets, 3.5 x 5", 4 x 6", 5 x 7", 8 x 10" photos, and 4 x 8" holiday cards
- Integrated photo scanner for print-to-print pictures
- Highly efficient for high-volume retail locations
- Connectivity options for remote monitoring, remote management, and credit card payment

**Does not include processing time.*

Portrait photofinishing

Offering the Sony-patented ProMatte finish, a powerful partner for professional portrait photo printing, brings an on-site, on-demand portrait photo printing service to your studio.

UP-D75
Digital Photo Printer

This 8 x 10 inch color photo printer integrates the most sought-after features used by portrait professionals such as a refined printing process, faster print speed, Sony's ProMatte finish and convenient stacking ability. The UP-D75 printer produces crisp and vibrant 8 x 10 inch and A4Plus size photo-quality prints with impressive continuous tone. The UP-D75 can produce ProMatte, Glossy or Texture finishes using the same media print pack.

- 8 x 10", 300 dpi photos in about 80* seconds
- ProMatte, Glossy or Texture finishes from one print pack
- Grey balance adjustments
- Built-in spool memory for greater productivity
- Hi-Speed USB 2.0 interface for fast image transfer
- Long-life print head

UP-GR700
Digital Photo Printer

This digital photo package printer produces high-quality, professional borderless 8 x 12 and 8 x 10 inch portraits in both glossy and ProMatte finishes. A high-capacity roll printer, it enables photographers to provide on-site, on-demand portrait printing services.

- Produces 8 x 10" and 8 x 12" prints
- Glossy and ProMatte finishes from the same media pack
  - 8 x 10" glossy prints in about 43* seconds
  - 8 x 12" glossy prints in about 48* seconds
  - ProMatte 8 x 10" prints in about 53* seconds
  - ProMatte 8 x 12" prints in about 58* seconds
- Front operation
- Includes "Professional Photos are protected by copyright" mark on media back

**Does not include processing time.*

Passport/ID photofinishing

Start your own passport and ID photo business the simple and effective Sony way – today!

UPX-C200
Wireless Digital Passport Photo System

The UPX-C200 Digital Printing System is the most modern, flexible and efficient passport ID and mini portrait system yet! With built-in Bluetooth® wireless technology, the system transfers images from its 4 megapixel camera to the printer without a docking station or cables. The compact printer can be used in the smallest of spaces.

- Auto preview
- Wireless Bluetooth technology
- Multiple print layout options
- Stores up to 200 images in Standard Memory
- Compact, space-saving design

UPX-C100
Digital Passport Photo System

Enabling you to enter today's passport ID photo market with minimal investment, the UPX-C100 is a turnkey solution, allowing you to start a profitable passport ID business from the moment it is installed. Consisting of a high quality 5 megapixel digital still camera and photo printer, the system couldn't be simpler to operate. Both the camera and printer (connected via a USB cable) are packed with sophisticated, yet easy-to-use functions and provide a truly simple and effective way to get started in the lucrative passport ID photo business.

- Auto preview
- Custom image capture setting
- Multiple layout options
- USB connectivity
- Compact, space-saving design

Take a closer look

At Sony, we develop our print media alongside our printers; each, naturally, complements the other. Use them together and you'll get the very best out of both. All Sony print media is watermarked with the "Print by Sony" logo, a hallmark of high quality printing, consistency and durability. Note: UP-GR700 photos watermarked with "Professional Photos are Protected by Copyright."

Here, you'll find more detailed specifications of the models featured in the previous pages of the brochure, together with a wide choice of print media allowing you to print what you want and how you want.

UPX-C100
Digital Still Camera

Resolution
1/2.5-inch CCD with 5M pixels (effective pixels 5/gross pixels 4.13)

Image format
Exif 2.2 compliance

Data compression
JPEG
Memory capacity
16MB (internal)

Image capacity
FULL (2576 x 1932 pixels): approx. 10 or more images,
HIGH (1280 x 960 pixels): approx. 40 or more images,
STD (832 x 624 pixels): approx. 73 or more images,
HIGH-ID (1280 x 960 pixels): approx. 40 or more images,
STD-ID (832 x 624 pixels): approx. 73 or more images

Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
403 dpi

Printing gradation
256 level, 8-bit digital signal processing each for Yellow, Magenta and Cyan

Paper size
UPC-X34: 3.5 x 4 inches
UPC-X46: 4 x 6 inches

Image size
Multiple layout options available
22 layout options for 4 x 6" size
17 layout options for 3 x 5" size

Printing time (approx.)
UPC-X34: 65 seconds
UPC-X46: 100 seconds

Print Media
Printing Packs
for the UPX-C100



10UPC-X34
Self-laminating
Color Printing Pack
Contents: 10 packs x 30 sheets
Paper size: 3.5 x 4 inches



UPX-C200
Digital Still Camera

Resolution
1/1.8-type IT CCD with 4M pixels (effective pixels 3.98/gross pixels 4.13)

Picture elements
2288 x 1712 pixels (HIGH),
1280 x 960 pixels (MID),
832 x 624 pixels (STD)

Recording medium
Internal memory

Data compression
JPEG

White balance
Auto/One Push/3000 K to 7000 K (500 K steps) selectable

Memory capacity
20 or more images (HIGH),
80 or more images (MID) ,
200 or more images (STD)

Iris
F2.8/F3.8/F5.0/F8.0 selectable (WIDE),
F4.8/F6.3/F8.3 selectable (TELE)

UP-DX100
Digital Photo Printer

Printing method
Dye sublimation printing

Printing resolution
403 dpi

Printing gradation
8-bit digital signal processing each for Yellow, Magenta and Cyan

Print tray capacity
10UPC-X34: 30 sheets
10UPC-X46: 25 sheets

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
110 W

Printing time (approx.)
UPC-X34: 65 seconds
UPC-X46: 100 seconds

*The system can be configured wirelessly with up to three UP-DX100 printers

Print Media
Printing Packs
for the UPX-C200



10UPC-X34
Self-laminating
Color Printing Pack
Contents: 10 packs x 30 sheets
Paper size: 3.5 x 4 inches

Specifications

Zoom
3x Optical
Focal length
f=5.7 to 17.1mm

Aperture
2 position
F2.8/F5.6 (wide) - F4.8/F9.6 (tele)

Shutter speed
Auto,
Manual 1/2 to 1/1000 second

Exposure
Auto, Manual

White balance
Auto, One Push, Manual
(3000 K to 7000 K, 500 K steps)

Focus
Auto focus (0.8 m and over)

Flash
Internal flash (GN6)

Sensitivity
ISO 100 equivalent

LCD display
2-inch* TFT color LCD
(110K pixels)

Interface
USB host port for the printer

Power supply
DC In (5.0 V) or 2AA batteries
Dimensions (W x H x D)
3 7/8 x 2 5/8 x 1 5/16 inches

Weight (approx.)
7 oz (without batteries)

Paper tray capacity
UPC-X34: 30 sheets
UPC-X46: 25 sheets

Interface
USB

Power requirements
AC 100 to 240 V, 50/60 Hz
Dimensions (W x H x D)
8 x 3 3/8 x 12 1/8 inches

Weight (approx.)
5 lb 15 oz

Safety standards
UL60950-1 listed, FCC Part15
Subpart B Digital Devices Class B,
CSA C22.2 No.60950-1, ICES-003
Issue 4 Class B apparatus,
EN60950-1,
EN55022 + 55024 (Class B),
EN61000-3-2 / EN6l000-3-3

Supplied accessories
Quick reference guide (1),
CD-ROM (Operation manual) (1),
AC Adaptor (1), Pigtail cable (1),
USB Cable (1), Camera Grip (1),
Alkaline AA Battery (2),
Paper Tray (X46 size) (1)
X34 size (1),
Cleaning Cartridge (1),

Tray Cover (1), Power Cables (2)

10UPC-X46
Self-laminating
Color Printing Pack
Contents: 10 packs x 25 sheets
Paper size: 4 x 6 inches*

*The measurement between
the two perforated lines

Exposure
Auto, aperture priority, manual EV
revised: -2.0 ~ +2.0 – 0.25 steps

Aperture
2.6 x Zoom, Auto focus

Shutter speed
1/2 to 1/1000 seconds

Sensitivity
Equivalent to ISO 100

LCD display
1.8-inch* cold polysilicone TFT
color LCD viewfinder

Digital interface
USB version 1.1
Video output
Composite video (1)

Wireless standard
Bluetooth version 1.1 Class 2

Data transfer time
Approx. 15 seconds:
2 1/4 x 2 1/4 inch image
Approx. 10 seconds:,
1 13/16 x 1 7/16 inch image

Power supply
NH-AA Battery (4) or AC adapter
(8.4 V DC)

Dimensions (W x H x D)
9 1/8 x 7 1/2 x 3 inches

Weight (approx.)
2 lb

Dimensions (W x H x D)
8 x 3 3/8 x 12 1/8 inches
Weight (approx.)
5 lb 15 oz

Safety standards
UL60950 listed,
FCC Part 15 Subpart C (247),
CSA No950, IC RSS-210,
ICES-003, EN60950,
EN300328-1, -2, EN301489-1, -17,
EN55022+55024 (class B)
EN61000-3-2 / EN61000-3-3, CCC
(GB4943 + GB9254 +17625.1),
Wireless Telegraph Law: [2001]
No.653, MIC (CISPR22 + CISPR24 +
IEC61000),
Ministry of Information and
Communication Republic of
Korea – No.2001-67

Supplied accessories
Operation manual (1 for UC,
2 for CED) (Basic version),
CD-ROM (1) (Printer driver,
Utility software,
Operation manual,
Installation guide for printer
driver), AC adapter (1),
AC power cable for AC adapter (1),
AC power cable for printer (1),
Paper tray: 10UPC-X46 size (1),
10UPC-X34 size (1),
Paper tray cover (1),
Paper holder (1),
Cleaning cassette (1),

NH-AA battery (4),
NH battery charger (1),
AC power cable for NH battery
charger (1 for CED),
Coin battery for camera (1)

10UPC-X46
Self-laminating
Color Printing Pack
Contents: 10 packs x 25 sheets
Paper size: 4 x 6 inches*

*The measurement between
the two perforated lines

**Viewable area; measured diagonally.*

UP-GR700
Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
300 dpi

Printing gradation
256 level, 8-bit digital signal processing each for Yellow, Magenta and Cyan

Image pixels transferred
8 x 10": 2444 x 3044 pixels
8 x 12": 2444 x 3644 pixels

Paper width
8 inches

Printing time (approx.)
8 x 10" glossy laminant:
approx. 43* seconds

8 x 10" ProMatte™ finish:
approx. 53* seconds
8 x 12" glossy laminant:
approx. 48* seconds
8 x 12" ProMatte:
approx. 58* seconds

Print capacity
8 x 10", 340 prints (170 per roll)
8 x 12", 300 prints (150 per roll)

Print Media Printing Pack for the UP-GR700

2UPC-R710
150 8 x 12" per roll
(300 prints per pack)
170 8 x 10" per roll
(340 prints per pack)
2 rolls print paper
2 rolls ink ribbon

UP-DR200
Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
330 dpi

Printing gradation
8-bit digital signal processing each for Yellow, Magenta and Cyan

Image pixels transferred
2UPC-R203: 1210 x 1728 dots
2UPC-R204: 1382 x 2048 dots
2UPC-R205: 1728 x 2380 dots
2UPC-R206: 2048 x 2724 dots

Print size
2UPC-R203: 3.5 x 5 inches
2UPC-R204: 4 x 6 inches

2UPC-R205: 5 x 7 inches
2UPC-R206: 6 x 8 inches

Printing time (approx.)	**Capacity**
2UPC-R203: 7.8* seconds	770
2UPC-R204: 8* seconds	700
2UPC-R205: 12.5* seconds	400
2UPC-R206: 14.5* seconds	350

Self-Laminating Color Printing Packs for the UP-DR200

2UPCR203
3.5 x 5 inches, 1,540 total prints,
2 rolls print paper and
2 rolls ink ribbon
(770 prints each)

UP-D75
Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
300 dpi

Printing gradation
8-bit digital signal processing each for Yellow, Magenta and Cyan

Image pixels transferred
Letter size (UPC-741):
3000 x 2400 dots
A4Plus size (UPC-747):
3508 x 2560 dots

Print size
Letter size (UPC-741):
8 x 10 inches

A4Plus size (UPC-747):
8 5/8 x 11 3/4 inches

Printing time (approx.)
Letter size (UPC-741): 80* seconds
A4Plus size (UPC-747): 90* seconds

Interface
Hi-Speed USB (USB 2.0)

Self-Laminating Color Printing Packs for the UP-D75

UPC-741
Letter Size: 8 x 10 inches
Contents:
72 sheets of print paper
Ink ribbon

**Does not include processing time.*

Driver software
Windows® 2000/XP Professional

Interface
Hi-Speed USB (USB 2.0)

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
3.0 to 1.3A max

Operating temperature
41 to 95˚F

Operating humidity
20% to 80%

Weight (approx.)
66 lb. 12 oz. not including 3 lb paper tray

Dimensions (W x H x D)
14.57 x 13.78 x 15.75 inches (including the maximum projecting parts)

Safety standards
UL60950-1 listed, EN60950-1 EMI: FCC part 15 Class A (US), Class B of EN55022 (CE)

Supplied accessories
Manual (1), Paper holder (1), Paper tray (1), AC power cord (1), Cleaning cartridge (1), CD-ROM (Windows printer driver software, Operating instructions PDF) (1)

Spool memory
For additional one picture

Interface
Hi-Speed USB (USB 2.0)

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
5 to 2.5 A max

Operating temperture
5˚ to 35˚C (41˚F to 95˚F)

Operating humidity
20% to 80%

Weight (approx.)
37 lb 5 oz

Dimensions (W x H x D)
11 ⅛ x 14 ⅛ x 18 ¼ inches (including the maximum projecting parts)

Safety standards
UL60950-1 listed, CSA C22.2 No. 60950-1 (cUL) (UC), EN60950-1 (CE)

Supplied accessories
Scrap receptacle, Print catcher, Paper spool, Cleaning ribbon, Operation instructions, CD-ROM (Driver software, Online manual)

2UPCR204
4 x 6 inches, 1,400 total prints, 2 rolls print paper and 2 rolls ink ribbon (700 prints each)

2UPCR205
5 x 7 inches, 800 total prints, 2 rolls print paper and 2 rolls ink ribbon (400 prints each)

2UPCR206
6 x 8 inches, 700 total prints, 2 rolls print paper and 2 rolls ink ribbon (350 prints each)

Spool memory
Two full images

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
Max 3.0/1.3 A

Stand by power
Less than 20 watts

Dimensions (W x H x D)
19 ½ x 7 x 18 ½ inches

Weight (approx.)
39 lb 11 oz

Bundled
Printer driver for Microsoft Windows 2000, XP Professional and Macintosh® OS

Safety standards
UL60950-1 listed, CSA C22.2 No.60950.1 (uCL) (UC), EN60950-1 (CE)

Supplied accessories
Ink ribbon holder (1), Paper tray (1), Paper cover (1), Fan cover (1), Bottom cover (1), Ferrite core (1), Thermal head cleaning kit (1), AC power cord (1), Operating instructions (1), Warranty card (1), CD-ROM (driver software, online manual) (1), Software License Agreement (1)

UP-CR10L SnapLab

Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
300 dpi

Printing gradation
256 (8-bit) digital signal processing each for Yellow, Magenta and Cyan

Image pixels transferred
2UPC-C13: 1100 x 1536 dots
2UPC-C14: 1248 x 1848 dots
2UPC-C15: 1536 x 2148 dots

Print size
2UPC-C13: 3.5 x 5 inches
2UPC-C14: 4 x 6 inches
2UPC-C15: 5 x 7 inches

Print speed (approx.)
2UPC-C13: 13** seconds
2UPC-C14: 16** seconds
2UPC-C15: 17** seconds

Print capacity
(per roll/ribbon cartridge)
2UPC-C13: 300 prints
2UPC-C14: 200 prints

Self-Laminating Color Printing Packs for the SnapLab

2UPC-C13
Paper size (after print) :
3.5 x 5 inches
Contents:
2 rolls print paper
(300 prints each)
2 rolls ink ribbon

UP-CX1

Digital Photo Printer

Printing method
Dye sublimation thermal transfer

Printing resolution
300 dpi

Printing gradation
8-bit digital signal processing each for Yellow, Magenta and Cyan

Image pixels transferred
3.5 x 5 in: 1100 x 1536 dots
4 x 6 in: 1248 x 1848 dots
5 x 7 in: 1536 x 2148 dots
4 x 8 in: 1248 x 2448 dots

Print size
2UPC-C13: 3.5 x 5 inches
2UPC-C14: 4 x 6 inches
2UPC-C15: 5 x 7 inches
2UPC-C48PF: 4 x 8 inches

Printing time (approx.)
3.5 x 5 in: 13** seconds
4 x 6 in: 16** seconds
5 x 7 in: 17** seconds
4 x 8 in: 20** seconds

Self-Laminating Color Printing Packs for the UP-CX1

2UPC-C13
3.5 x 5 in, 600 total prints
2 rolls print paper
(300 prints each)
2 rolls ink ribbon

UPA-PC500

Digital Photofinishing Terminal

Operating system
Microsoft® Windows® XP embedded

Display
15-inch* XGA (1024 x 768) TFT LCD with touchscreen

CPU
Intel® Pentium® 4 2.4 GHz
Memory: 512 MB
HDD: 80 GB

Input media
Memory Stick®, Memory Stick Duo™, Memory Stick PRO™, Memory Stick PRO Duo™,

CompactFlash, SmartMedia, SD Memory Card, miniSD, MultiMedia Card (MMC), RS-MMC, xD-Picture Card, USB memory device, CD, DVD

Paper specifications for the receipt printer
Core diameter: ½ to ¾ inch

Compact PictureStation™

Digital Photofinishing System

Operating system
Microsoft® Windows® XP embedded

Display
15-inch* XGA (1024 x 768) TFT LCD with touchscreen

CPU
Intel® Pentium® 4 2.4 GHz
Memory: 512 MB
HDD: 80 GB

Input media
Memory Stick®, Memory Stick Duo™, Memory Stick PRO™, Memory Stick PRO Duo™,

CompactFlash, SmartMedia, SD Memory Card, miniSD, MultiMedia Card (MMC), RS-MMC, xD-Picture Card, USB memory device, CD, DVD

Supported Peripherals:
Ships with Scanner, UP-DR150 (1 unit) or UP-DR200 (1 unit),

Deluxe PictureStation

Digital Photofinishing System

Operating system
Microsoft® Windows® XP embedded

Display
15-inch* XGA (1024 x 768) TFT LCD with touchscreen

CPU
Intel® Pentium® 4 2.4 GHz
Memory: 512 MB
HDD: 80 GB

Input media
Memory Stick®, Memory Stick Duo™, Memory Stick PRO™, Memory Stick PRO Duo™, CompactFlash, SmartMedia,

SD Memory Card, miniSD, MultiMedia Card (MMC), RS-MMC, xD-Picture Card, USB memory device, CD, DVD

Supported Peripherals:
3 printer version ships with: Scanner, UP-DR150 (2 unit) or UP-DR200 (2 unit);

**Viewable area; measured diagonally.*
***Does not include processing time.*

2UPC-C15: 172 prints

Paper feed method
Roll paper, automatic loading from paper holder

Interface
Memory Stick®, Memory Stick Duo™, Memory Stick PRO™, Memory Stick PRO Duo™, SD, MMC, CF, MD, xD, SM
USB Host: USB (A) x 1 for USB Mass Storage Class Device
PC Connection: USB (B) x1 for PC
Expansion Slot: Compact Flash type 1/11 x 1
Expansion Terminal: RS-232C (D-sub 9pin) x 1 for future peripheral support
LCD Display
8-inch* touch sensitive TFT color LCD

Dimensions (W x H x D)
10 7/8 x 11 7/8 x 14 15/16 inches, excluding protruding parts.

Weight (approx.)
24 lb, 4 oz excluding paper tray

Safety standards
UL60950-1 listed, CSA C22.2 No.60950-1, EN60950-1 (CE)

Supplied accessories
Paper tray (1), Paper holder (1), Paper core (1), Adaptor left (1), Adaptor right (1), Power cord (1), Cleaning cartridge (1), Ferrite core (1), CD-ROM (driver software, PDF files of multi-language manuals) (1), Software License Agreement (1), Operating instructions (1), Warranty card (1), Service and Customer Support Info (1)

2UPC-C14
Paper size (after print) :
4 x 6 inches
Contents:
2 rolls print paper
(300 prints each)
2 rolls ink ribbon

2UPC-C15
Paper size (after print) :
5 x 7 inches
Contents :
2 rolls print paper
(172 prints each)
2 rolls ink ribbon

Print capacity
(per roll/ribbon cartridge)
3.5 x 5 in: 300 prints
4 x 6 in: 200 prints
5 x 7 in: 172 prints
4 x 8 in: 150 prints

Interface
Hi-Speed USB (USB 2.0)

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
3 to 1.3 A max

Operating temperature
5˚C to 35˚C (41˚F to 95˚F)

Operating humidity
20% to 80%

Dimensions (W x H x D)
10 7/8 x 10 3/8 x 15 inches
(excluding extruding parts)

Weight (approx.)
23 lb 2 oz (excluding paper tray)

Safety standards
UL/cUL60950-1 listed, EN60950-1, FCC/IC Class B Digital Device, EN55022 Class B + EN55024 + EN61000-3-2 + EN61000-3-3
AS (EMC) AS/NZS CISPR 22 Class B, VCCI Class B, JIS C61000-3-2

Supplied accessories
Manual (1), Paper holder (1), Paper tray (1), AC power cord (1), Cleaning cartridge (1), CD-ROM (Windows printer driver software, Operating instructions PDF) (1)

2UPC-C14
4 x 6 in, 400 total prints
2 rolls print paper
(200 prints each)
2 rolls ink ribbon

2UPC-C15
5 x 7 in, 344 total prints
2 rolls print paper
(172 prints each)
2 rolls ink ribbon

2UPC-C48PF
4 x 8 in, 300 total prints
2 rolls print paper
(150 prints each)
2 rolls ink ribbon

Roll diameter: 2 inch
Paper width: 1/4 inch
Supported peripherals
A maximum of up to 4 Sony photo printers and one scanner can be supported, UP-DR150 (up to 4 units), UP-D75 (1 unit), UP-XC1 (up to 4 units) Flatbed scanner

Power requirements
AC 100 to 240 V, 50/60 Hz
Power consumption
5.0 A to 3.0 A max

Operating temperature
5˚C to 35˚C (41˚F to 95˚F)

Operating humidity
20% to 80%

Dimensions (W x H x D)
16 x 19 x 9 5/8 inches

Weight (approx.)
50.8 lb

Safety standards
UL60950-1 listed,
CSA No.60950-1,
EN60950-1,
FCC Part15 Class A,
ICES-003 Class A,
EN55022 Class B + EN55024,
C-Tick EN55022 Class B

Supplied accessories
Cabinet key (2),
Eject pin (for ejecting CD) (1),
Installation guide (1),
Operating instructions (1),
User's guide (1),
Warranty booklet (1)

and UP-GR700 (1 unit)
A maximum of up to four Sony photo printers and one scanner can be supported. UP-DR150 (up to 4 units), UP-DR200 (up to 4 units), UP-CX1 (up to 4 units), UP-GR700 (1 unit), UP-D75 (1 unit)

Power requirements
AC 100 to 240 V, 50/60 Hz

Power consumption
13.0A to 7.0A Max

Operating temperature
5˚C to 35˚C (41˚F to 95˚F)

Dimensions (W x H x D)
18 x 56 x 23 inches

Supplied accessories
Terminal Accessories,
Printer Accessories,
PictureStation Cabinet,
Cabinet Keys (2),
Scanner Cover, Power Strip

UP-D75 (1 unit); and optional UP-CXI greeting card printer
4 printer version ships with:
Scanner, UP-DR150 (2 unit) or UP-DR200 (2 unit), UP-CX1 (1 unit), and UP-D75 (1 unit)
A maximum of up to four Sony photo printers and one scanner can be supported. UP-DR150 (up to 4 units), UP-DR200 (up to 4 units), UP-CX1 (up to 4 units), UP-GR700 (1 unit), UP-D75 (1 unit)

Power requirements
AC 100 to 240 V, 50/60 Hz

4 Printer power consumption
20.0A to 12.0A Max

Operating temperature
5˚C to 35˚C (41˚F to 95˚F)

Dimensions (W x H x D)
38 x 60 x 26 inches

Supplied accessories
Terminal Accessories, Printer Accessories, PictureStation Cabinet, Cabinet Keys (2), Scanner Cover, Power Strip

**Viewable area; measured diagonally.*

SONY

Services from Sony
working with you, working for you.

Recognizing that every company and every challenge is unique, we offer a complete and comprehensive range of services all the way through consulting, planning, implementation, training, servicing, maintenance and support. Choose exactly what's right for you, when and where you need it.

Sony Training Services

A range of off-the-shelf or customized training services from basic operation through to high-level technical maintenance.

Sony Support Services

Fully integrated and customized support for products and systems throughout their operational life, combining proactive and reactive technical services.

click: sony.com/dpf

© 2008 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measurements are approximate and may vary. Sony, SnapLab, ProMatte, the Print by Sony logo, the Sony logo, Memory Stick, Memory Stick Duo, Memory Stick PRO and Memory Stick PRO Duo are registered trademarks of Sony Corporation. Bluetooth is a trademark of Bluetooth SIG. Windows, Microsoft are trademarks of Microsoft Corporation. Intel, Pentium are trademarks of Intel. All other trademarks are the property of their respective owners.